

Frames

adjustable height

Our Adjustable frames offer a simple solution for mounting plant on flat roofs. The frames are made from 40mm x 40mm galvanised box section giving you a very durable system.

The frames come in a full range of widths from 600mm to 2metres utilising a common 1.2metre long sliding mounting.

With our unique double socket foot it is easy to join 2 modules together if a larger system is required onsite

The common rails are locked into position using 2 x M8 Nuts & Bolts, which creates a simple clamping system



Standard Adjustable Frame Set

Condenser Clamps Available
Sold Separately



Holding
2,000 Kgs

100% UK Manufacture
100% UK Sourced Materials



Single Socket
Foot



Double Socket
Foot

Product Code	Model	Length (mm)	Height Inc foot (mm)
COMBI 44	600 Pitch Adjustable U Frame Set Inc: 2x Frame, 4x 350 feet & 2x Common Rails	680	275 – 375
COMBI 45	800 Pitch Adjustable U Frame Set Inc: 2x Frame, 4x 350 feet & 2x Common Rails	880	275 – 375
COMBI 46	1000 Pitch Adjustable U Frame Set Inc: 2x Frame, 4x 350 feet & 2x Common Rails	1080	275 – 375
COMBI 47	1500 Pitch Adjustable U Frame Set Inc: 2x Frame, 4x 350 feet & 2x Common Rails	1580	275 – 375
COMBI 71	600 Pitch Adjustable U Frame Set Inc: 2x Frame, 4x 500 feet & 2x Common Rails	680	280 – 380
COMBI 72	800 Pitch Adjustable U Frame Set Inc: 2x Frame, 4x 500 feet & 2x Common Rails	880	280 – 380
COMBI 73	1000 Pitch Adjustable U Frame Set Inc: 2x Frame, 4x 500 feet & 2x Common Rails	1080	280 – 380
COMBI 74	1500 Pitch Adjustable U Frame Set Inc: 2x Frame, 4x 500 feet & 2x Common Rails	1580	280 – 380

Product Code	Model	Length (mm)	Height Inc foot (mm)
COMBI 76	600 Adjustable U Frame Only	680	
COMBI 77	800 Adjustable U Frame Only	880	
COMBI 78	1000 Pitch Adjustable U Frame Only	1080	
COMBI 79	1500 Pitch Adjustable U Frame Only	1580	
COMBI 25	1.2 Common Rail	1200	40mm x 40mm box

MATERIAL SPECIFICATION
Frames are manufactured from 40mm x 40mm x 2.5mm wall thickness - Galvanised SHS – BS EN ISO 1461